

No.2 KOHLER ROAD, SANSHUI CENTRAL INDUSTRIAL PARK, LEPING TOWN, SANSHUI DIST., FOSHAN, GUANGDONG, PRC POST CODE: 528137 廣東省佛山市三水區樂平鎮三水中心工業園區科勒大道2號 郵編:528137

8# MENGSHAN RD, ECONOMIC DEVELOPMENT ZONE OF HUANTAI, ZIBO, SHANDONG, CHINA POST CODE: 256410 山東省淄博市桓台經濟開發區蒙山路8號 郵編:256410

NO.1 KOHLER STREET, ECONOMIC DEVELOPMENT ZONE OF FAKU COUNTY, SHENYANG LIAONING PROVINCE, PRC POST CODE: 110400 遼寧省瀋陽市法庫經濟開發區科勒大街1號 郵編:110400

### **REMOVE EXISTING** LAVATORY

- Turn off the water supply to the faucet. · Open the faucet valves, then disconnect the
- supply lines. Disconnect the drain assembly and remove
- the trap.
- Remove the existing lavatory.

# 拆除舊面盆

- 打開龍頭閥門,然後除開供水管。
- 再旋開排水裝置,並拿開彎管
- 移走舊面盆


• 關掉水龍頭的供水源。

### **INSTALL NEW LAVATORY**

- Cut the template on the cutout line. Position the template on the countertop to ensure clearance between the lavatory, faucet, and backsplash.
- Verify cabinet clearance beneath the countertop.



- Re-check the clearance between the lavatory, faucet, backsplash, and cabinet. Adjust the template accordingly.
- Drill a 13mm hole on the inside of the cutout opening.
- Cut the opening in the countertop along the inside edge of the pencil line.
- Temporally position the lavatory in the opening, and adjust to fit.
- CAUTION: Risk of personal injury or product damage. Large lavatories are very heavy. Get help lifting the lavatory into place.
- Trace a pencil line around the outside edge of the lavatory.
- Remove the lavatory.
- Install the faucet and drain according to the manufacturers instructions.
- Apply two beads of sealant to the inside of
- the pencil line. Spread the sealant evenly with a putty knife
- Carefully position the lavatory in the cutout,
- and press down firmly. CAUTION: Risk of personal injury or



- Immediately wipe away any excess sealant, and fill any voids as needed.
- Verify that the lavatory has not moved out of position.
- Allow the sealant to cure for at least 30 minutes before proceeding.
- Connect the faucet supply lines.
- Connect the drain assembly. Open the faucet valves, and check for
- leakage Clean up with a non-abrasive cleaner.
- After installing the dropper, put the decorative cover in the sink hole.

side of the basin as follows



• 安裝落水頭後,把裝飾蓋放在落水孔

(注意:38014T-NA不能放在盆的前面)

# 兩個配件按如下方式放在面盆的前邊和左邊

## NOTE

- This product cannot be used with large cap drain; • It is recommended to use Kohler pop up drain or Kohler

(Note: 38014T-NA cannot be placed in front of

 When using the click drain, remove the decorative cap before opening/closing the drain; as shown below:

- 1. 此產品不能使用大帽蓋下水器; 2. 此產品推薦使用科勒提拉桿下水器或科勒線纜下水器;
- 3. 當使用彈跳下水器時,須先取出裝飾蓋後才可以開關下水



### IMPORTANT CONSUMER **INFORMATION (CARE AND CLEANING**)

To keep your lavatory looking new, make sure you rinse it out 為保持面盆光潔如新‧須確保每次使用後徹底沖洗乾淨‧切勿 thoroughly after each use. **DO NOT USE ABRASIVES** on this product, as they will scratch and ruin the surface. Stubborn stains, paint, or tar can be removed with turpentine or paint thinner.

Do not use the product in the water below 0°C.

CAUTION: Please do not use hard materials (like scouring pad) to clean product surface, especially the

## 用戶須知 (護理和清潔)

使用腐蝕性的清潔劑,以免刮花及破壞面盆的表面。要清除頑 固汙垢,油漆或柏油,可使用松油或油漆稀釋劑。

不要在0℃以下的水環境中使用。

警告:請勿使用鋼絲球等硬質材料擦洗產品表面,特別

# **SERVICE PARTS**



裝飾蓋

28919T-NA 短收納盒



1528236-T2-A

© Copyright Kohler China Investment Co., Ltd. 2022 © 版權為科勒(中國)投資有限公司所有 2022



# 安裝新面盆

- 將切割圖沿切割線切出。 • 將切割圖放在盥洗台上,確保面盆、水
  - 查核盥洗台下的儲物櫃也有足夠空間

龍頭和防濺擋板之間有足夠的距離。



- 用炭筆沿切割圖在盥洗檯面劃線。
- 再次檢查面盆、水龍頭、防濺水板及儲 物櫃的空間及距離。如有需要可調校切 割圖的位置。
- 用一個13mm的鑽頭,在切割口內側鑽
- 沿著自切割圖勾劃出來的鉛筆線內側切
- 暫將面盆放入檯面開口,校正位置。
- 小心:提防身體受傷或損壞產品。因 大型面盆相當重,須找人幫您一起搬



- 用炭筆沿面盆外緣在盥洗台上劃線。
- 然後將面盆移開。 • 按照製造商的指引,安裝水龍頭和排水
- 沿炭筆導線內側圖兩滴封邊膠
- 用塗油灰刀將其抹勻。 小心地將面盆置於檯面切口適當位置
- 小心:提防身體受傷或損壞產品。因 大型面盆相當重,須找人幫您一起搬 動及安放。
  - 立即擦去多餘的封邊膠,如面盆外緣與 檯面間有縫隙,即用膠填密。 • 檢查面盆的位置準確。
  - 最少待三十分鐘,讓封邊膠乾透後,方
  - 可繼續進行安裝。 連接水龍頭供水管。
  - 連接排水裝置。 開啟水龍頭閥門,檢查有否滲漏。
  - 用非腐蝕性清潔劑來清潔。

